



0



STERIPLUS[™] 20

INTEGRATED SYSTEM WITH PRELIMINARY SHREDDING AND STEAM STERILIZATION OF YOUR BIOHAZARDOUS WASTE

lesalys

The **STERIPLUS™** systems from **Tesalys** are the ideal solution to inactivate your biohazardous waste safely on-site. Its integrated shredding system **TESASHRED™** not only reduces the volume and mass of waste, but also ensures waste is fully processed.







STERIPLUS[™] 20

integrated system with preliminary shredding and steam sterilization of your biohazardous waste

LOAD CAPACITY (VOLUME)



USAGE DATA

| WATER | |
|----------------------|------------------------------------------|
| REQUIREMENTS | Water 4-8° TH |
| CONSUMPTION | 5 to 6 liters/cycle |
| ELECTRICITY | |
| REQUIREMENTS | 380-400 V III N, 50 Hz/60 Hz, 10 kW |
| CONSUMPTION | 2 kWh |
| DRAIN | 32 mm ø internal (heat-resistant) (1.2") |
| STEAM/COMPRESSED AIR | Produced by the integrated steam |

generator and air compressor; no external connection required.

| AVERAGE LOAD CAPACITY (WEIGHT) | 2 to 2.5 kg of waste per cycle* (4-5 lbs.) 4 to 5 kg of waste per hour (8-11 lbs.) |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| MAXIMUM LOAD CAPACITY (WEIGHT) | 5 kg of waste per cycle (11 lbs.) 10 kg of waste per hour (22 lbs.) Maximum permitted weight using Tesaly 12 L containers |
| LOADING CHAMBER USEFUL Dimensions | 320 x 247 mm (width x depth) (12.5" x 9.7") useful height = 270 mm (10.6") |
| TOTAL CYCLE TIME | 50-55 minutes |
| PRODUCTION | Up to 5 kg/h (average) (11 lbs./h) Up to 10 kg/h (maximum) (22 lbs./h) |
| EXTERNAL DIMENSIONS (H x W x D) | 1,150 mm x 1,205 mm x 885 mm (H x W x D) (45.2" x 47.5" x 34.8") |
| NET WEIGHT | 490 kg (1,080 lbs.) |
| LOADING CHAMBER | Stainless steel with PTFE non-stick coating |
| TREATMENT CHAMBER | AISI 304L stainless steel |
| STEAM GENERATOR | AISI 304L stainless steel (chamber), highly corrosion-resistant Hastelloy® |
| WATER SOFTENER | Optional (exterior) |
| WATER BOOSTER PUMP AND AIR Compressor | Integrated |
| WASTE SHREDDER | AISI 304L stainless steel (structure), high-strength steel (blades) |
| PIPING | Stainless steel/PTFE flexible hosing |
| CHASSIS | Painted steel |
| BODYWORK | Composite material/Painted steel |
| CYCLE TRACEABILITY Through printout | Integrated |
| USB PORT | Included |

20 liters of waste per cycle*





CONIFER SERVICES

56 Terranova, Mandi Road, Mehrauli, New Delhi, India Phone: +91 9953333225 Email: info@coniferservices.com

www.coniferservices.com